

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 3

Claim Amendments:

Claims 131, 132, 134, 135, 137, 139, 141, 143 and 145-190 remain in the application. Claims 133, 136, 138, 140, 142 and 144 have been cancelled. Claims 131, 134, 137, 139, 141, 143, 145, 151, 152, 156, 158, 159, 165, 166, 168, 181, 182 and 190 are amended as follows:

Listing of Claims:

1-130 (cancelled)

131. (currently amended) A vehicular window assembly suitable for use in a vehicle, said window assembly comprising:

a glass panel having a first surface and an opposing second surface;

~~an attachment member~~ a gasket for attachment to said glass panel for mounting said window assembly to the vehicle, said gasket comprising at least one of a rigid polymeric material and a flexible polymeric material, said gasket disposed adjacent at least a perimeter portion of said first surface;

said glass panel and said ~~attachment member~~ gasket joined by an adhesive layer;

said adhesive consisting essentially of urethane, said urethane adhesive disposed between said first surface of said glass panel and said ~~attachment member~~ gasket, said layer of urethane adhesive cured to form a load bearing joint suitable for use on the vehicle;

said layer of cured urethane adhesive bonding said ~~attachment member~~ gasket to said first surface of said glass panel prior to installation of said assembly in the vehicle and without exposure of said bonded ~~attachment member~~ gasket on said second surface of said panel; and

wherein said joint including said urethane adhesive is capable of withstanding a localized tensile load of at least 5 pounds per square inch without failure due to separation from the underlying glass, said localized tensile load being applied in a temperature range of -

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 4

40° to 100°C, said cure of said joint being accelerated by at least one of a) heating and b) at least one chemical agent; and

wherein said assembly further includes an attachment member adhesively attached to said first surface of said glass panel at a location spaced from said gasket.

132. (previously added) The vehicular window assembly of claim 131 wherein said joint is capable of withstanding a localized tensile load of at least 40 pounds per square inch without failure.

133. (cancelled)

134. (currently amended) The vehicular window assembly of claim ~~133~~ 132 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 6 square inches.

135. (previously added) The vehicular window assembly of claim 131 wherein said joint is capable of withstanding a localized tensile load of at least 80 pounds per square inch without failure.

136. (cancelled)

137. (currently amended) The vehicular window assembly of claim ~~136~~ 135 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 6 square inches.

138. (cancelled)

139. (currently amended) The vehicular window assembly of claim ~~138~~ 131 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 6 square inches.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 5

140. (cancelled)

141. (currently amended) The vehicular window assembly of claim ~~140~~ 139 wherein said cure of said joint is accelerated by heating with at least one of induction heating and infrared heating.

142. (cancelled)

143. (currently amended) The vehicular window assembly of claim 131 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 1 square inch.

144. (cancelled)

145. (currently amended) The vehicular window assembly of claim ~~144~~ 131 wherein said cure of said joint is accelerated by heating with at least one of induction heating and infrared heating.

146. (previously added) The vehicular window assembly of claim 131 further comprising a layer of at least one of an adhesive promoter and a primer disposed between said glass panel and said layer of adhesive.

147. (previously added) The vehicular window assembly of claim 146 wherein said at least one of said adhesion promoter and said primer is selected from the group consisting of silane compounds, titanium coupling agents, zirconium coupling agents, and moisture-curable urethane prepolymers.

148. (previously added) The vehicular window assembly of claim 146 wherein the thickness of said layer of at least one of said adhesion promoter and said primer is from about 0.01 mils to about 3.5 mils.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 6

149. (previously added) The vehicular window assembly of claim 146 wherein the thickness of said layer of at least one of said adhesion promoter and said primer is from about 0.05 mils to about 2 mils.

150. (previously added) The vehicular window assembly of claim 146 wherein the thickness of said layer of at least one of said adhesion promoter and said primer is from about 0.1 mils to about 1.0 mils.

151. (currently amended) The vehicular window assembly of claim 131 further comprising a glass frit layer disposed on said glass panel, said glass frit layer being disposed between said first surface of said glass panel and said layer of cured adhesive such that said layer of cured adhesive bonds said ~~attachment member~~ gasket directly to said glass frit layer.

152. (currently amended) The vehicular window assembly of claim 131 wherein the thickness of said adhesive layer disposed between said ~~attachment member~~ gasket and said glass panel is from about 0.01 mm to about 4.0 mm.

153. (previously added) The vehicular window assembly of claim 152 wherein the thickness of said adhesive layer is from about 0.25 mm to about 2.0 mm.

154. (previously added) The vehicular window assembly of claim 153 wherein the thickness of said adhesive layer is from about 0.5 mm to about 1.0 mm.

155. (previously added) The vehicular window assembly of claim 131 wherein said attachment member is selected from the group consisting of mounting members, hinges, clevises, latches, lift brackets, division bars, positionable members, guide tracks, handles, guide pins, strut-mounting hardware, strikers, struts, power-mounting hardware, track members, rails, latch members, antennas, wiper mounts, sealing members, cosmetic articles, pin components, and hinge members.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 7

156. (currently amended) A bonded vehicular assembly suitable for use in a vehicle, said assembly comprising:

a glass substrate having a first surface and an opposing second surface;

~~an attachment member comprising a material selected from the group consisting of metal, plastic, and combinations thereof, said attachment member being selected from the group consisting of mounting members, hinges, clevises, latches, lift brackets, division bars, positionable members, guide tracks, handles, guide pins, strut mounting hardware, strikers, struts, power mounting hardware, track members, rails, latch members, antennas, wiper mounts, sealing members, cosmetic articles, pin components, and hinge members~~ a gasket for attachment to said glass substrate for mounting said vehicular assembly to a vehicle, said gasket comprising at least one of a rigid polymeric material and a flexible polymeric material, said gasket disposed adjacent at least a perimeter portion of said first surface; and

a layer of urethane adhesive disposed between and bonding said first surface of said glass substrate to said ~~attachment member~~ gasket, said urethane adhesive disposed between said first surface of said glass panel and said ~~attachment member~~ gasket, said layer of urethane adhesive cured to form a load bearing joint suitable for use on the vehicle;

said layer of cured urethane adhesive bonding said ~~attachment member~~ gasket to said first surface of said glass substrate prior to installation of said assembly in the vehicle and without exposure of said bonded ~~attachment member~~ gasket on said second surface of said substrate; and

wherein said joint including said urethane adhesive is capable of withstanding a localized tensile load of at least 5 pounds per square inch without failure due to separation from the underlying glass;

said localized tensile load being applied in a temperature range of -40°C to 100°C;

said cure of said joint being accelerated by at least one of a) heating, and b) at least one chemical agent.

157. (previously added) The bonded vehicular assembly of claim 156 wherein said cure of said joint is accelerated by heating with at least one of induction heating and infrared heating.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 8

158. (currently amended) The bonded vehicular assembly of claim 156 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 6 square inches.

159. (currently amended) The bonded vehicular assembly of claim 156 wherein said ~~attachment member~~ gasket has a surface area mounting footprint of less than about 1 square inch.

160. (previously added) The bonded vehicular assembly of claim 156 wherein said joint is capable of withstanding a localized tensile load of at least 40 pounds per square inch without failure.

161. (previously added) The bonded vehicular assembly of claim 156 wherein said joint is capable of withstanding a localized tensile load of at least 80 pounds per square inch without failure.

162. (previously added) The bonded vehicular assembly of claim 156 further comprising a layer of at least one of an adhesion promoter and a primer disposed between said glass substrate and said layer of urethane adhesive.

163. (previously added) The bonded vehicular assembly of claim 162 wherein said at least one of said adhesion promoter and said primer is selected from the group consisting of silane compounds, titanium coupling agents, zirconium coupling agents, and moisture-curable urethane prepolymers.

164. (previously added) The bonded vehicular assembly of claim 156 wherein said assembly is a movable vehicular window assembly.

165. (currently amended) The bonded vehicular assembly of claim ~~164~~ 156 wherein said assembly further comprises a glass frit layer disposed on said glass substrate, said glass frit layer being disposed between said first surface of said glass substrate and said layer of

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 9

urethane adhesive such that said layer of urethane adhesive bonds said ~~attachment member~~
gasket directly to said glass frit layer.

166. (currently amended) The bonded vehicular assembly of claim 156 wherein said ~~attachment member comprises~~ assembly also includes a hinge having a first portion and a second portion that is movable with respect to said first portion, and wherein said first portion is bonded to said first surface of said glass substrate by an amount of said urethane adhesive disposed between and contacting said first portion and said glass substrate.

167. (previously added) The bonded vehicular assembly of claim 166 wherein said second portion of said hinge is affixed to a vehicular mounting surface.

168. A method of adhering ~~an attachment member~~ a gasket to a glass surface for use in a vehicle, said method comprising:

providing a substrate having a glass surface and an opposing second surface;

providing ~~an attachment member~~ a gasket to be adhered to said glass surface, said ~~attachment member~~ gasket adapted for attachment to said glass surface for mounting the substrate and gasket to a vehicle, said gasket having a mounting surface of less than about six (6) square inches and comprising at least one of a rigid polymeric material, said gasket disposed adjacent at least a perimeter portion of said first surface;

providing a urethane adhesive;

depositing an effective amount of said urethane adhesive on at least one of said ~~attachment member~~ gasket mounting surface and said glass surface;

positioning said ~~attachment member~~ gasket and said substrate such that said urethane adhesive is disposed between and contacting said ~~attachment member~~ gasket and at least a portion of said glass surface of said substrate without exposure of said ~~attachment member~~ gasket on said opposing second surface of said substrate; and

curing said urethane adhesive to form a load bearing joint between said ~~attachment member~~ gasket and said portion of said glass surface of said substrate including accelerating said curing by at least one of a) heating and b) at least one chemical agent whereby said joint

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 10

which is formed is capable of withstanding a localized tensile load of at least five (5) pounds per square inch when said load is applied at a temperature in the range of -40°C to 100°C.

169. (previously added) The method of claim 168 wherein said adhesive comprises an isocyanate component and a polyol component including a high amine density plural amine compound, and wherein said method further comprises, prior to said depositing said adhesive, a step of:

mixing said isocyanate component and said polyol component.

170. (previously added) The method of claim 169 wherein said high amine density plural amine compound is in an amount of from about 2% to about 20% by weight of said polyol component and said adhesive further comprises at least one filler agent in at least one of said isocyanate component and said polyol component, wherein said filler agent is in an amount of from about 15% to about 50% of the total weight of said polyol and isocyanate components.

171. (previously added) The method of claim 170 wherein said filler agent is in an amount of from about 20% to about 30% of the total weight of said polyol and said isocyanate components.

172. (previously added) The method of claim 170 wherein said filler agent is selected from the group consisting of silicates, silica, calcium carbonate, talc, and combinations thereof.

173. (previously added) The method of claim 169 wherein said isocyanate component comprises compounds with isocyanate functionality and said polyol component comprises compounds with hydroxy and/or amino functionality, and wherein the ratio of isocyanate functionality to hydroxy and amino functionality is from about 0.9 to about 2.0.

174. (previously added) The method of claim 173 wherein said ratio of isocyanate functionality to hydroxy and amine functionality is from about 1.03 to about 1.4.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 11

175. (previously added) The method of claim 174 wherein said ratio of isocyanate functionality to hydroxy and amino functionality is from about 1.1 to about 1.3.

176. (previously added) The method of claim 169 wherein said high amine density plural amine compound is a compound having an amine to carbon ratio of from about 1.0 to about 0.25:1 with the provisos that (i) the compound contains at least 3 amine groups except if said compound is aromatic then said compound contains at least 2 amine groups, and (ii) the compound contains from 2 to 24 carbon atoms.

177. (previously added) The method of claim 176 wherein said high amine density plural amine compound has a molecular weight of from about 115 to about 5000.

178. (previously added) The method of claim 177 wherein said high amine density plural amine compound has a molecular weight of from about 210 to about 290.

179. (previously added) The method of claim 169 wherein said high amine density plural amine comprises a reaction product of (i) at least one of pentaerythritol, glucose, and sucrose, and (ii) at least one member selected from the group consisting of ammonia and amino alkanes of the formula $C_xH_nNH_2$, where x range from 1 to 20 and n is such that the alkane is saturated.

180. (previously added) The method of claim 179 wherein x ranges from about 1 to about 6.

181. (currently amended) The method of claim 168 further comprising, prior to depositing said adhesive, a step of:

depositing a layer of at least one of an adhesion promoter and a primer to at least one of said glass surface and said ~~attachment member~~ gasket mounting surface.

182. (currently amended) The method of claim 168 wherein the thickness of said adhesive disposed between said ~~attachment member~~ gasket and at least a portion of said glass surface is from about 0.01 mm to about 4.0 mm.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 12

183. (previously added) The method of claim 182 wherein the thickness of said adhesive is from about 0.25 mm to about 2.0 mm.

184. (previously added) The method of claim 183 wherein the thickness of said adhesive is from about 0.5 mm to about 1.0 mm.

185. (previously added) The method of claim 168 wherein said depositing step is performed by robotic deposition.

186. (previously added) The method of claim 168 wherein said depositing step is performed by utilizing a dispense metering unit and a mixing unit.

187. (previously added) The method of claim 186 wherein said mixing unit is a mix tube in association with a sequential reverse mixer.

188. (previously added) The method of claim 186 wherein said providing urethane adhesive is performed by delivering said adhesive through thermally controlled lines to said dispense metering unit.

189. (previously added) The method of claim 168 wherein said heating is performed by a method selected from the group consisting of induction curing, infra red heating, and combinations thereof.

190. (currently amended) The method of claim 168 further including providing said substrate with a layer of frit on said glass surface, depositing said urethane adhesive on at least one of said ~~attachment member~~ gasket mounting surface and said frit layer, and positioning said ~~attachment member~~ gasket and said substrate such that said urethane adhesive is disposed between and contacting said ~~attachment member~~ gasket and at least a portion of said frit layer.

Applicant : Jeffrey A. Lewno
Serial No. : 10/054,016
Page : 13

Terminal Disclaimer:

A Terminal Disclaimer to obviate the double patenting rejection, and the required disclaimer fee, are submitted herewith under 37 C.F.R. 1.321. The Terminal Disclaimer has been signed by an officer of the assignee of the present application.